

OAK RIDGE NATIONAL LABORATORY

Operated by

UNION CARBIDE NUCLEAR COMPANY

Division of Union Carbide Corporation



Post Office Box X

Oak Ridge, Tennessee



R-5128

ORNL
CENTRAL FILES NUMBER
58-10-60

DATE: October 17, 1958
SUBJECT: Survey of Low Enrichment Molten-Salt Reactors
TO: Listed Distribution
FROM: H. G. MacPherson

COPY NO. 52

External Transmittal Authorized

Distribution Limited to Recipients Indicated

Abstract

A rough survey of the nuclear characteristics of graphite-moderated molten-salt reactors utilizing an initial complement of low enrichment uranium fuel has been made. Reactors can be constructed with initial enrichments as low as 1.25% U-235; initial conversion ratios of as high as 0.8 can be obtained with enrichment of less than 2%. Highly enriched uranium would be added as make-up fuel, and such reactors could probably be operated for burnups as high as 60,000 Mwd/ton before buildup of fission products would make replacement of the fuel desirable. A typical circulating fuel reactor of this class might contain an initial inventory of 3600 tons of 1.8% enriched uranium, operated at 640 Mw (thermal), and generate a net of 260 Mw (electrical). The total fuel cycle cost would be approximately 1.3 mills/kwhr, of which 1.0 mill is burnup of enriched U-235.

NOTICE

This document contains information of a preliminary nature and was prepared primarily for internal use at the Oak Ridge National Laboratory. It is subject to revision or correction and therefore does not represent a final report.

The information is not to be abstracted, reprinted or otherwise given public dissemination without the approval of the ORNL Patent Branch, Legal and Information Control Department.

RELEASE APPROVED
BY PATENT BRANCH

6-24-60 [Signature]
DATE SIGNATURE

cy. 52

Errata for CF 58-10-60

Please make the following changes in your copy of CF 58-10-60:

Page 1 (Cover Sheet) Make change in line 10 of abstract

From: 3600 tons of 1.8%

To: 36 tons of 1.8%

Page 2 Make change in next to last line

From: 8.54×10^{20}

To: 8.54×10^{22}

Page 3 Make change in line 18

From: $\sqrt{\frac{S}{n}}$

To: $\sqrt{\frac{S}{M}}$

SURVEY OF LOW ENRICHMENT MOLTEN-SALT REACTORS

To survey the field of low enrichment graphite-moderated reactors a number of calculations have been made with the four-factor formula $k_{\infty} = \eta \epsilon p f$. The following fuel salt was considered:

| | <u>mole %</u> |
|-------------------|---------------|
| UF ₄ | 20 |
| Li ⁷ F | 70 |
| BeF ₂ | 10 |

This salt has a melting point of about 900°F. It is probably more corrosive than one mole % fuel, but is probably satisfactory for use with INOR-8. The atomic concentrations were as follows at 600 - 650°F, per L. A. Mann:

| | |
|----|-------------------------------------|
| Li | - 175.7 x 10 ²⁰ atoms/cc |
| Be | - 25.12 x 10 ²⁰ atoms/cc |
| U | - 50.22 x 10 ²⁰ atoms/cc |
| F | - 426.8 x 10 ²⁰ atoms/cc |

The slowing down power of the salt is 0.0228 cm⁻¹, composed of contribution as follows:

| | |
|----------|-------|
| Fluorine | .0149 |
| Li | .0051 |
| Be | .0028 |

The concentration of UF₄ is 2.62 g/cc; that of uranium is 1.98 g/cc. Graphite was assumed to be of density 1.7, with 8.54 x 10²⁰ atoms/cc, and a slowing down power of 0.0631 cm⁻¹. The graphite was assumed to have a $\sigma_a = 0.0045$ barns.

In the four-factor formula, η is taken for convenience to be that for U-235, while the thermal utilization factor f is defined as the proportion of thermal absorption in U-235. Thus, using cross sections derived from Fig. 2.3, page 2.20, of ORNL-2500, Part 2, η for U-235 is taken as $2.47 \times \frac{528}{650}$ or $\eta = 2.00$. Effective thermal fission cross sections and absorption cross sections are assumed to be 528 barns and 650 barns, respectively, corresponding to neutron temperatures of 600°C .

The fast fission factor was assumed to be 1.02, since the values calculated for graphite lattices vary from 1.02 to 1.04. This assumption is sufficiently accurate for survey purposes.

For the calculation of the resonance escape probability, the resonance integral was calculated from,

$$\sigma_r = 3.8 \left(\frac{\Sigma_s}{N_o} \right)^{0.42} + 24.7 \frac{S}{M}$$

In this formula, $\frac{\Sigma_s}{N_o}$ is the scattering cross section in barns per uranium atom within the fuel channel, and $\frac{S}{M}$ is the surface area of the fuel channel per gram of U-238 in the channel. The first term is the same as the resonance integral for an infinite medium of the fuel salt composition. This formula, involving the first power of $\frac{S}{M}$ instead of $\sqrt{\frac{S}{\eta}}$, was used because it is more logically extrapolated to the case of dilution of uranium with fuel salt. For uranium metal this reduces to the familiar $\sigma_r = 9.25 \times 24.7 \frac{S}{M}$. In the fuel considered here, $\frac{\Sigma_s}{N_o} = 43.3$, and $\sigma_r = 18.5 + 24.7 \frac{S}{M}$.

A series of reactors having tubular fuel channels on a square array is considered. The spacing of these channels was arbitrarily taken as 8 in. center to center, and the calculations are made for various volume fractions of fuel in the graphite from 0.05 to 0.25. The following table gives the fuel channel diameter, the value of $\frac{S}{M}$, the value of σ_r , and the value of the resonance escape probability p for the different volume fractions. p is calculated from $p = e^{-A}$ where A is given by,

$$A = \frac{N_u \sigma_r F}{(1 - F)(\xi \Sigma_s)_g + F(\xi \Sigma_s)_{\text{salt}}}$$

where N_u is the U-238 atom density in the fuel channel and F is the volume fraction of fuel in the core. Numerically,

$$A = \frac{50.22 \times 10^{20} \sigma_r F \times 10^{-24}}{0.0631 (-1-F) + 0.0228 F}$$

Table I

| <u>F</u> | <u>D</u> | <u>S/M</u> | <u>σ_r</u> | <u>p</u> | <u>$\eta \epsilon p$</u> |
|----------|----------|------------|------------------------------|----------|-------------------------------------|
| .05 | 2.08 in. | .382 | 27.95 barns | 0.891 | 1.82 |
| .075 | 2.54 | .313 | 26.25 | 0.848 | 1.73 |
| .10 | 2.94 | .271 | 25.20 | 0.807 | 1.65 |
| .15 | 3.60 | .221 | 23.97 | 0.733 | 1.495 |
| .20 | 4.15 | .192 | 23.25 | 0.653 | 1.332 |
| .25 | 4.65 | .171 | 22.73 | 0.584 | 1.191 |

The thermal utilization factor is given by,

$$f = \frac{F e N_u \hat{\sigma}_a^u}{F e N_u \hat{\sigma}_a^u + F N_u \sigma_a^{238} + F \Sigma_a^{\text{salt}} + (1 - F) \Sigma_a^g \gamma}$$

where e is the enrichment, $\hat{\sigma}_a^u$ is the effective absorption cross section for U-235, and γ is the thermal flux disadvantage factor. For this survey, γ is assumed to be 2.0, which seems a reasonable value based on ORNL-2500. This simplifying assumption was made to avoid calculating the flux distribution, and probably is the roughest approximation made in this survey. Numerically the above equation reduces to,

$$f = \frac{3.22 F e}{3.22 F e + 0.0137 F + 0.0028 F + 0.000768 (1 - F)}$$

An easy computational form is,

$$\frac{1}{f} = 1 + \frac{0.0157 + \frac{0.00077}{F}}{3.22 e}$$

To calculate the enrichment necessary to achieve a given k_∞ , the following transformations are made,

$$k_\infty = \eta \epsilon p f$$

$$\frac{1}{f} = \frac{\eta \epsilon p}{k_\infty}$$

$$\text{and } e = \frac{0.0157 + \frac{0.00077}{F}}{3.22 \left(\frac{\eta \epsilon p}{k_\infty} - 1 \right)}$$

The conversion factor is calculated as follows,

$$R_c = \frac{(1 - p) + p \times (\text{proportion of thermal absorptions in U-238})}{p \times (\text{proportion of thermal absorptions in U-235})}$$

$$\text{From } k_\infty, B^2 \text{ is obtained from } B^2 = \frac{k_\infty - 1}{M^2}$$

and M^2 is taken as,

$$M^2 = \frac{\tau_{\text{graphite}}}{1 - F} + L_{\text{graphite}}^2 \times (\text{proportion of thermal absorptions occurring in graphite})$$

The correction for τ_{graphite} is an approximate one, but not too important numerically. τ_{graphite} is taken as 324 cm^2 and L_{graphite}^2 is 2950 cm^2 .

From B^2 the dimensions of a minimum volume cylindrical core were calculated using a reflector savings of 2 ft. This is less than used in ORNL-2500, but may still be optimistic because some fuel must be used in the reflector to cool it.

Table II gives the results of calculations for six values of the volume fraction of fuel in the core and for two values of k_{∞} . The volume of fuel in the core should be evaluated in terms of the external volume for a circulating fuel reactor, which is about 0.56 cu ft per thermal megawatt, or 360 cu ft for a 260 Mw (electrical) plant. It is evident that one must pay for conversion ratios above 0.8 with enrichments of over 2%.

The selection of an economically optimum reactor of this type requires a knowledge of the method of chemical reprocessing and its cost, and a way of calculating the effect of poisoning by buildup of fission products. The latter problem was looked at briefly, using as a basis the calculations of Blomeke and Todd (ORNL-2127), and assuming a buildup of Pu sub infinity as defined in the Brookhaven Geneva Paper 461. For the very long exposures it is probable that the one-group calculations can not give a good answer because of the large buildup of absorbing Pu isotopes. However, it might be possible to operate a reactor such as Case 8 of Table II for as

long as 30 years at 640 Mw (thermal) without a need for the U-235 inventory to increase by more than a factor of two, and with a breeding ratio averaging greater than 50%, without any reprocessing.

For purposes of estimating the fuel cycle cost, a life of 10 years without reprocessing was assumed. For this period, the U-235 concentration would probably not have to be increased over its initial value, and the breeding ratio should average at least 60%.

Applying the formula of ORNL-2500, but using the thermal cycle of the reference design molten-salt reactor (CF-58-5-3), the chemical reprocessing charges and fuel inventory charges are 0.034 mill/kwhr and 0.14 mill/kwhr, respectively. Ten-year depreciation and capital charges on the base salt amount to 0.093 mill/kwhr. Burnup of U-235 would be ~1.0 mill/kwhr at a conversion ratio of 0.6. Thus, total fuel cycle costs would be approximately 1.3 mills/kwhr.

This reactor was based on Case 8 of Table II, using a total fuel volume of 600 ft³ and an inventory of 36 tons of uranium of 1.8% enrichment. The ten-year reprocessing cycle represents a fuel life of approximately 60,000 Mwd/ton.

More accurate calculations are needed to confirm the above conclusions.

Table II

| Case | Vol fraction of fuel in core | | Percent Enrichment of uranium | Vol of fuel in core cu ft | Uranium in core kg | Critical mass of U-235 | Initial conversion Ratio |
|------|------------------------------------|--------------|-------------------------------------|---------------------------------|--------------------------|------------------------------|--------------------------------|
| | F | k_{∞} | e | V_f | M_u | M_{235} | R_c |
| 1 | 0.05 | 1.05 | 1.30 | 395 | 22,100 | 298 | .546 |
| 2 | | 1.10 | 1.45 | 143 | 8,000 | 116 | .492 |
| 3 | 0.075 | 1.05 | 1.25 | 427 | 23,900 | 298 | .635 |
| 4 | | 1.10 | 1.39 | 167 | 9,350 | 130 | .600 |
| 5 | 0.10 | 1.05 | 1.275 | 445 | 24,900 | 318 | .707 |
| 6 | | 1.10 | 1.46 | 179 | 10,000 | 146 | .668 |
| 7 | 0.15 | 1.05 | 1.525 | 474 | 26,600 | 405 | .796 |
| 8 | | 1.10 | 1.80 | 197 | 11,000 | 198 | .780 |
| 9 | 0.20 | 1.05 | 2.24 | 520 | 29,100 | 652 | .865 |
| 10 | | 1.10 | 2.88 | 206 | 11,540 | 332 | .865 |
| 11 | 0.25 | 1.05 | 4.36 | 575 | 32,200 | 1400 | .900 |
| 12 | | 1.10 | 7.05 | 240 | 13,430 | 952 | .865 |

Distribution

1. L. G. Alexander
2. C. J. Barton
3. E. S. Bettis
4. J. P. Blakely
5. F. F. Blankenship
6. A. L. Boch
7. W. F. Boudreau
8. E. J. Breeding
9. W. E. Browning
10. D. O. Campbell
11. W. H. Carr
12. G. I. Cathers
13. R. A. Charpie
14. D. A. Douglas
15. W. K. Ergen
16. H. L. Falkenberry
17. A. P. Fraas
18. W. R. Grimes
19. H. W. Hoffman
20. W. H. Jordan
21. G. W. Keilholtz
22. F. Kertesz
23. B. W. Kinyon
24. M. E. Lackey
25. J. A. Lane
26. W. J. Larkin, AEC, ORO
27. H. G. MacPherson
28. R. E. MacPherson
29. W. D. Manly
30. E. R. Mann
31. L. A. Mann
32. W. B. McDonald
33. H. J. Metz
34. R. P. Milford
35. F. C. Moesel, AEC, Washington.
36. G. J. Nessel
37. W. R. Osborn
38. J. T. Roberts
39. H. W. Savage
40. A. W. Savolainen
41. M. J. Skinner
42. E. Storto
43. J. A. Swartout
44. A. Taboada
45. R. E. Thoma
46. D. B. Trauger
47. F. C. VonderLage
48. G. M. Watson
49. A. M. Weinberg
50. G. D. Whitman
51. J. Zasler
52. Laboratory Records, R.C.

Errata for CF 58-10-60

Please make the following changes in your copy of CF 58-10-60:

Page 1 (Cover Sheet) Make change in line 10 of abstract

From: 3600 tons of 1.8%

To: 36 tons of 1.8%

Page 2 Make change in next to last line

From: 8.54×10^{20}

To: 8.54×10^{22}

Page 3 Make change in line 18

From: $\sqrt{\frac{S}{n}}$

To: $\sqrt{\frac{S}{M}}$