



---

# Damage Analysis and Fundamental Studies

Quarterly Progress Report  
October-December 1984

---

February 1985

---

U.S. Department of Energy  
Office of Energy Research  
Office of Fusion Energy  
Washington, DC 20545  
E&R No. AT-15-O2-O3-O4

## CONTENTS

|   | <u>Page</u> |
|---|-------------|
| Foreword  | iii         |
| CHAPTER 1: IRRADIATION TEST FACILITIES  |             |
| 1. <u>RTNS-II IRRADIATIONS AND OPERATIONS (LLNL)</u>  | 2           |
| <p>Irradiations were performed on 13 different experiments during this quarter. The new materials lab has been completed. The Fifth U.S.-Japan Steering Committee meeting was held December 13, 1984, in Tokyo.</p> <p>Clint Logan, Facility Manager, will transfer from RTNS-II to another LLNL program on December 31, 1984. Dale Heikkinen has been appointed Acting Manager.</p>              |             |
| CHAPTER 2: DOSIMETRY AND DAMAGE PARAMETERS  | 4           |
| 1. <u>SPINEL IRRADIATIONS IN THE OMEGA WEST REACTOR (ANL)</u>   | 5           |
| <p>Dosimetry measurements and damage calculations are reported for several short irradiations of spinel in the Omega West Reactor.</p>  |             |
| 2. <u>UPDATING OF THE SPECTER AND DOSFILE COMPUTER CODES (ANL)</u>  | 9           |
| <p>Detailed instructions are given for users of the SPECTER computer code for radiation damage and the DOSFILE code for dosimetry and damage data from fusion irradiations. Both codes are resident at the National Magnetic Fusion Energy Computer Center.</p>   |             |
| 3. <u>HELIUM PRODUCTION IN REACTOR-IRRADIATED COPPER AND TITANIUM, AND EVIDENCE FOR A COPPER THREE-STAGE REACTION (Rockwell International and ANL)</u>  | 13          |
| <p>Helium generation measurements have been performed for Cu and Ti samples irradiated in HFIR and ORR. The results are discrepant with ENDFIB-V cross sections. The copper results, plus correlated discrepancies in <math>^{65}\text{Zn}</math> reaction rates measured in the irradiated copper samples, suggest the presence of a thermal neutron three-stage reaction process in copper.</p> |             |
| CHAPTER 3: <b>REDUCED</b> ACTIVATION MATERIALS  | 17          |
| 1. <u>CROSS SECTIONS FOR REDUCED ACTIVATION STUDIES (HEDL)</u>  | 15          |
| <p>A new activation library containing reaction cross sections for 337 isotopes and about 6000 reactions was created.</p>   |             |
| CHAPTER 4: FUNDAMENTAL MECHANICAL BEHAVIOR  | 27          |
| 1. <u>DETERMINATION OF THE HARDENING RESPONSE IN THREE SURROGATE MATERIALS USING BALL MICROHARDNESS TECHNIQUES (U. of California, Santa Barbara)</u>  | 28          |
| <p>The ball microhardness test technique was applied to three heat-treatable alloys which were age hardened to simulate a radiation hardening response. The good agreement with tensile data indicates the viability of the technique to monitor changes in the constitutive behavior of a material as a function of environmental history.</p>   |             |

CONTENTS (Cont'd)

|  | <u>Page</u> |
|--|-------------|
| 2. <u>PREDICTIONS OF FRACTURE TOUGHNESS IN IRRADIATED AISI 316 BASED ON A TENSILE-TOUGHNESS CORRELATION (HEDL)</u>   | 33          |
| <p>A model for tensile-toughness correlations is presented which appears to be valid for radiation-hardened stainless steels. Tensile data from both ducts and cladding of 20% cold worked 316 are used to predict that sufficient toughness is retained in this steel for both fission and fusion reactor applications.</p>   |             |
| 3. <u>THE INFLUENCE OF COMPOSITION ON MICROSTRUCTURAL EVOLUTION AND MECHANICAL PROPERTIES OF IRRADIATED Fe-Cr-Ni TERNARIES (HEDL)</u>  | 41          |
| <p>The tensile strength of irradiated Fe-Cr-Ni alloys depends strongly on the Ni content in the 25-45% range but not on the Cr content. EM examination indicates that the Ni sensitivity is caused by a decrease in void concentration and an increase in spinodal development with increasing nickel.</p>   |             |
| CHAPTER 5: CORRELATION METHODOLOGY   | 48          |
| 1. <u>DEPTH-DEPENDENT SWELLING IN 14-MeV ION-IRRADIATED P7 ALLOY (U. of Wisconsin)</u>   | 49          |
| <p>The alloy P7, a low-impurity, single-phase version of AISI 316 (major elements only), was irradiated with 14-MeV Ni ions to 100 dpa. Void swelling exceeding 30% was measured.</p>  |             |
| 2. <u>THE ROLE OF PHOSPHORUS IN THE SWELLING AND CREEP OF IRRADIATED AUSTENITIC ALLOYS</u>   | 56          |
| <p>Phosphorus is much more effective than other solutes in delaying swelling and irradiation creep of austenitic alloys. It increases the vibrational frequency and diffusivity of matrix solvent atoms, and increases the equilibrium vacancy concentration orders of magnitude by reducing the vacancy formation energy.</p>   |             |
| 3. <u>CROSS-SECTION TECHNIQUE FOR ION-IRRADIATED HT-9 FERRITIC STEEL (U. of Wisconsin)</u>   | 63          |
| <p>A cross-section technique (using iron plating) has been developed for heavy-ion-irradiated HT-9.</p>  |             |
| 4. <u>THE MAGNITUDE AND DISTRIBUTION OF THE EXCESS INTERSTITIAL FRACTION DURING HEAVY ION IRRADIATION (U. of Wisconsin)</u>  | 68          |
| <p>The magnitude of the excess interstitial fraction (<math>c_i</math>) in the ion deposition region increases as the incident ion energy decreases. For low energy (&lt; 5 MeV) ion irradiations, there exists no part of the ion range free from the presence of excess interstitials; while, for the high energy (14 MeV) case, <math>c_i</math> appears to be negligible at depths less than 1.2 <math>\mu</math>m.</p>  |             |
| CHAPTER 6: FUNDAMENTAL STUDIES OF SPECIAL PURPOSE MATERIALS  | 76          |
| 1. <u>ION IRRADIATION OF COPPER AND COPPER ALLOYS TO 40 DPA AT 100-400°C (U. of Wisconsin)</u>   | 77          |
| <p>Pure copper and several copper alloys were found to be resistant to void formation following ion irradiation to a calculated peak damage level of 40 dpa at 100-400°C. The absence of a significant void population is probably due to the low oxygen content in the foils, and also the absence of helium during the irradiation.</p>  |             |
| 2. <u>PHYSICAL PROPERTIES OF HIGH-STRENGTH, HIGH-CONDUCTIVITY COPPER ALLOYS (U. of Wisconsin and Washington State University)</u>  | 85          |
| <p>Vickers microhardness, electrical resistivity, and miniature tensile specimen measurements were made on AMLIRC and AMAX-MZC copper alloys in the cold-worked plus aged and annealed conditions. It was determined that the strength of these alloys is due largely to their cold-worked nature; this strength is lost when recrystallization occurs (~475°C for a one-hour anneal). A linear correlation between microhardness and yield strength was observed for both alloys.</p> |             |